FOG AND STRAIGHT NOZZLE (ALUMINIUM)

These combination nozzles are ideal for use on monitors or fire hoses.
It is excellent on fog and straight stream flow pattern.
Most widely used type of nozzle with easy handling and light weight.
Lightweight aluminium with black hard anodizing is free from corrosion.
A general straight type along with adjustable flow type is available.

SL-10S / SL-11S

SL-10NW

SL-10NWQ

SL-9N

SL-11D

SL-11Q

SL-11NWQ

SL-11NW

Model	Size	Flow Rate (@7 barg.)	L(mm)	W(kg)	Remarks
SL-9N	NH 1"	130 LPM	112	0.5	for Hose Reel
SL-10S	NH 1½"	313 LPM	130	0.3	for Hydrant
SL-11S	NH 2½"	625 LPM	155	0.5	
SL-10NW	NH 1½"	535 LPM	137	0.5	for Hydrant & Fire Truck Fluorescent, Green, Yellow
SL-11NW	NH 2½"	900 LPM	172	1.0	
SL-10NWQ	Machino 40 (1½")	535 LPM	150	0.6	
SL-11NWQ	Machino 65 (2½")	900 LPM	180	1.3	
SL-11D	NH 2½"	380-570-760-945 LPM	300	2.0	for Hydrant / Adjustable Flow
SL-11Q	Machino 65 (2½")		300	2.2	

* BSP, BS336, STORZ, GOST connection available